




"KING EDGAR" ★

General arr.



003275-003281-0138



© 2020

Lloyd's Register
Foundation

S.S. "EMPIRE GAMBIA" GENERAL ARRANGEMENT.

SCALE 1/8" = ONE FOOT.

DIMENSIONS:- 425'-0" B.P. x 56'-0" x 27'-9" TO 2° DK. x 36'-9" TO UPPER DK.



DOCKING BRIDGE

7'-6" TO 7'-0" ABOVE UPPER DK.

UNDERSIDE OF BRIDGE DK. OVER MESS ROOM.

WATERWAY & AIRWAY PASSAGE COVERED

WITH SPRAYED ASBESTOS.

2 RAIL STANCHIONS. TOP TUBE 1 1/2" DIA.

BOTTOM ROD 3/4" DIA.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

6" DIA. CY. TO DECK CREWS MESS.

BOAT DK & CASING TOP

BOAT DK. 7'-0" TO 7'-6" ABOVE UPPER DK.

2 RAIL STANCHIONS. 3 1/2" HIGH TOP TUBE 1 1/2" DIA.

ONE INTERMEDIATE ROD 3/4" DIA.

EXPANDED STEEL DK. OVER ALUMINUM COVERED WITH

5/8" OREGON PINE WOOD.

DECK IN ACCORDANCE WITH APPROVED CONSTRUCTION

LAWS & NO. 100. LASH LASH WITH COLOURED CEMENT.

SIDEWALKS 10" DIA. EXCEPT WHERE MARKED OTHERWISE.

ENGINE CASING 7'-0" AT SIDE 9'-0" AT CR. ABOVE UPPER DK.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

CREWS SPACE AFT - MECHANICAL VENTILATION HEATING

MIDSHIP ACCOMMODATION - MODIFIED SYSTEM OF MECHANICAL

VENTILATION, CONSISTING OF SMALL INDEPENDANT

SUPPLY FANS IN THE VENTILATORS TO EACH

CABIN & EXHAUST FANS IN THE PASSAGEWAY VENTS.

STEAM HEATING IN MIDSHIP ACCOMMODATION.

LOWER BRIDGE DECK

7'-0" TO 7'-6" ABOVE UPPER DK.

EXPANDED STEEL DK. OVER ALUMINUM COVERED WITH

5/8" OREGON PINE WOOD.

DECK IN ACCORDANCE WITH APPROVED CONSTRUCTION

LAWS & NO. 100. LASH LASH WITH COLOURED CEMENT.

SIDEWALKS 10" DIA. EXCEPT WHERE MARKED OTHERWISE.

ENGINE CASING 7'-0" AT SIDE 9'-0" AT CR. ABOVE UPPER DK.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

NAVIGATING BRIDGE

7'-0" TO 7'-6" ABOVE LOWER BRIDGE

EXPANDED STEEL DK. COVERED WITH 5/8" OREGON

PINE WOOD. DECK IN ACCORDANCE WITH APPROVED CONSTRUCTION

LAWS & NO. 100. LASH LASH WITH COLOURED CEMENT.

SIDEWALKS 10" DIA. EXCEPT WHERE MARKED OTHERWISE.

ENGINE CASING 7'-0" AT SIDE 9'-0" AT CR. ABOVE UPPER DK.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.

44 PERSONS.